

**FAL-EX-0072 HAZARDOUS LIGHTING SERIES 72 WATTS**

<b>Delivered Lumens</b>	9,108 lm
<b>Wattage</b>	72 W
<b>Delivered Efficacy</b>	126.5 lm/W
<b>Voltage</b>	AC100-277V
<b>Available Color Temp.</b>	3000-5000K
<b>CRI</b>	>70
<b>Optional CRI*</b>	>80
<b>Beam Angle</b>	120°
<b>Weight**</b>	11 kg (24.3 lb)
<b>Operating Temperature</b>	-40° to 45°
<b>Dimensions</b>	1200mm×136mm×85mm (47.2"×5.4"×3.4")
<b>Dimming</b>	n/a
<b>Material</b>	Copper-free aluminum, Shock and vibration resistant tempered glass
<b>Warranty</b>	5 Years
<b>Standard Installation</b>	Surface/Wall, Ceiling, Suspension, Pole, Clamp
<b>Listing</b>	Class 1, Division 2 – Groups A,B,C,D   Class 2, Division 2 – Groups F,G   Class 3

\*>80 CRI is standard only for 3000K CCT

\*\*Fixture weights specified are displayed for the standard configuration for the model. Weight fluctuation will be dependent on desired configuration.

\*\*\*Other features, not listed, can be added per customer request.