



## SLD-PK-0300 PARKADE SERIES 280 WATTS

<b>Delivered Lumens</b>	38,040 lm
<b>Wattage</b>	280 W
<b>Delivered Efficacy</b>	136 lm/W
<b>Voltage</b>	AC100-480V
<b>Available Color Temp.</b>	2700-6500K
<b>L70 (TM21)</b>	145,000 hours
<b>CRI</b>	>70
<b>Optional CRI</b>	>80, >90
<b>Beam Angle</b>	10°, 25°, 60°, 120°, 131°*, Type II, Type III
<b>Weight**</b>	10.6 kg (23.3 lb.)
<b>Operating Temperature</b>	-40° to 55°C
<b>Dimensions</b>	Ø504mm×258mm (Ø19.8"×10.1")
<b>Dimming</b>	0-10V Optional
<b>Material</b>	Aluminum, Sheet Metal, High Strength PC
<b>Warranty</b>	5 Years
<b>Standard Installation</b>	Surface / Pole / Suspension Mount
<b>Additional Features***</b>	Remote &/or Powerline Dimmability, Motion Sensors, Surge Protection

\*Glare-free only for beam angles of 131°

\*\*Fixture weights specified are displayed for the standard configuration for the model. Weight fluctuation will be dependent on desired configuration.

\*\*\*Other features, not listed, can be added per customer request.